

*The best ever passbook and document printer from IBM*



## 9068-A01/A03 Multi-Purpose Passbook Printer

**Faster, quieter, smaller, and lighter**

**Provides easy-to-use interface and sophisticated paper handling**

**Application compatible with IBM finance printers and more**



**IBM offers the ultimate in passbook and document printer that provides high print throughput, versatility, and high usability. The IBM 9068 models A01 and A03 are 24-wire impact printers that attach to PCs and provide the following benefits.**

Improves the productivity of the operator by providing one of the highest print performance in the industry. Prints on variety of print media including passbooks, slips, checks, multi-part cutforms, and envelopes that come in wide range of sizes and thicknesses commonly used by financial institutions. Sophisticated paper handling capability frees operators from such things as aligning documents, adjusting for paper thickness, and positioning the paper for print registration. Quiet operation (less than 54dB) will not interrupt conversation. Allows more freedom in selecting software solution through the support of both IBM and non-IBM emulations. Long life ink ribbon cartridge (10 M characters) frees operators from the need to replace ribbon cartridges up to 6 months depending on the usage. This also helps reduce the cost of ownership. Allows more freedom in the selection of attachment ports by having serial RS232, parallel, and USB ports on each printer. This also provides the migration path from one attachment to the other. Optional REMS feature eliminates operation step for the operator to swipe passbooks through magnetic stripe reader by reading and encoding magnetic stripes on a passbook automatically under program control. Model A01 comes with one year warranty, model A03 comes with three year warranty.



<b>Passbook Size (cover open w/o mag)</b>	Horizontal Fold : 102mm-241mm( W )x 99mm-210mm( L ) max 1.8mm thick Vertical Fold : 127mm-241mm( W )x 99mm-210mm( L ) max 1.8mm thick
<b>Cutform Size</b>	66mm-241mm( W )x 69mm-711mm( L ) max 6 ply
<b>Print Span</b>	3mm to 238mm from left paper edge
<b>Print Speed (10 cpi)*</b>	330cps( fast draft ) 275cps( standard ) 146cps( quality )
<b>Operating System</b>	IBM DOS 5.0 or later, IBM OS/2® 2.0 or later, Windows NT® 3.51 and 4.0, Windows® 95, Windows 98, Windows 2000
<b>Emulation</b>	IBM 4722, IBM ProPrinter X24, Olivetti PR2, others upon request
<b>REMS (option)</b>	F/2F, 210bpi, IBM 3600/4700, ISO, and DIN types ( supported for bi-directional serial and USB attachment )
<b>Document Alignment</b>	Automatic
<b>Paper Thickness Adjust</b>	Automatic
<b>Dimension &amp; Weight</b>	380mm( W )x 313mm( D )x 185mm( H ) 8.5kg( w/o REMS )9.5kg( w/REMS )

\* Print speed may vary depending on the font selected.

IBM and OS/2 are trademarks of International Business Machines Corporation in the United States and/or other countries. Windows NT and Windows are registered trademarks of Microsoft Corporation.



**IBM Japan Ltd.**

Finance Solutions  
1623-14, Shimo Tsuruma, Yamato-shi, Kanagawa 242  
02-01 Printed in Japan

Pictures in this catalogue may differ from actual products. Specification of products are subject to change without notice.



G 5 1 8 - 5 2 6 6 - 0 2